




MPC15-20 SERIES

PEDESTRIAN PALLET TRUCK

TECHNICAL SPECIFICATIONS



TRUCK DIAGRAM



TECHNICAL DATA

Specifications Table

GENERAL	1.2	MODEL DESIGNATION			MPC15	MPC20
	1.1	Manufacturer			YALE	YALE
	1.3	Drive type			Full-Electric	Full-Electric
	1.4	Operator type			Pedestrian	Pedestrian
	1.5	Rated capacity/rated load	Q	t	1.5	2.0
	1.6	Load centre distance	c	mm	600	600
	1.9	Wheelbase	y	mm	1197/1267	1197/1267
Weight	2.1	Service weight including battery		kg	116.5/123	119/125.5
Wheels	3.1	Tyres, front/rear			PU (Polyurethane)	PU (Polyurethane)
	3.2	Tyre size, front		mm	Ø140*55	Ø140*55
	3.3	Tyre size, rear		mm	Single wheel: Ø80*93	Single wheel: Ø80*93
				mm	Double wheel: Ø80*70	Double wheel: Ø80*70
	3.5	Number of wheels, front/rear (X = driven)			1x+2/4	1x+2/4
	3.7	Tread, rear	b11	mm	385/520	385/520
Dimensions	4.4	Lift	h3	mm	115	115
	4.9	Height drawbar in driving position min./max.	h14	mm	820/1150	820/1150
	4.15	Height, fork lowered	h13	mm	82±2	82±2
	4.19	Overall length	l1	mm	1552/1622	1552/1622
	4.20	Length to face of forks	l2	mm	1150/1220	1150/1220
	4.21	Overall width (single / wide / dual)	b1	mm	550/685	550/685
	4.22	Fork dimensions (Height*width*length)	s/e/l	mm	58/160/1150 or 1220	58/160/1150 or 1220
	4.25	Distance between fork-arms	b5	mm	550/685	550/685
	4.32	Ground clearance, centre of wheelbase	m2	mm	22/137 or 24/13	22/137 or 24/13
	4.34.1	Aisle width for pallets 1000 × 1200 crossways	Ast	mm	2376	2376
	4.34.2	Aisle width for pallets 800 × 1200 lengthways	Ast	mm	2257	2257
	4.35	Turning radius	Wa	mm	1353/1426	1353/1426
Performance	5.1	Travel speed, laden/unladen		km/h	4.0/4.5	4.0/4.5
	5.1.1	Travel speed, laden/unladen, backwards		km/h	4.0/5.0	4.0/5.0
	5.2	Lift speed, laden/unladen		mm/s	23/38.7	22.5/32.8
	5.3	Lowering speed, laden/unladen		mm/s	39/28	40.9/27.3
	5.7	Gradeability, laden/unladen		%	6%/20%	6%/20%
	5.8	Max. gradeability - 1.6 km/h, with / without load		%	6%/20%	6%/20%
	5.10	Traveling brake			Regenerate	Regenerate
		Brake			Electromagnetic	Electromagnetic
	6.1	Drive motor, S2 60 min rating		kW	DC Brushless 0.75Kw	DC Brushless1.0Kw
	6.2	Lift motor S3 15% rating		kW	DC 0.8KW	DC 0.8KW
	6.3	Battery according to DIN 43531/35/36 A,B,C, no			No	No
	6.4	Battery voltage / nominal capacity K5		V/Ah	48V/10Ah/48V/15Ah	48V/10Ah/48V/15Ah
	6.5	Battery weight		kg	4.5/5.9	4.5/5.9
	6.6	Energy consumption acc. to VDI cycle		kWh/h	0.42	0.42
Additional Data	8.1	Type of drive unit			Electric	Electric
	10.7	Sound level at the driver's ear according to EN 12053		dB	< 70dB	< 70dB

OPTIONS TABLE

Available Options

DESCRIPTION	STANDARD	OPTIONAL
CONSTRUCTION	STANDARD	OPTIONAL
Metal Key Switch Start		X
Keyless Start	X	
Remote Control		X
Pin Code on tiller		X
Galvanization		X
LIFT OPTIONS - FRONT END EQUIPMENT	STANDARD	OPTIONAL
1150mm x 550mm / 21.7" x 45.3" Welded Type - Standard Tip Forks	X	
800mm x 550mm / 21.7" x 32" Welded Type - Standard Tip Forks		X
1150mm x 685mm / 27" x 45.3" Welded Type - Standard Tip Forks		X
1220mm x 685mm / 27" x 48" Welded Type - Standard Tip Forks		X
1000mm x 685mm / 27" x 39" Welded Type - Standard Tip Forks		X
1000mm x 550mm / 39" x 21.7" Welded Type - Standard Tip Forks		X
Load Back Rest		X
Retractable Cargo Belt		X
CHASSIS - DRIVE & STEER TIRES	STANDARD	OPTIONAL
80 x 70mm / 3.14" x 2.7" Tandem Polyurethane Load Wheels		X
80 x 93mm / 3.14" x 3.66" Single Polyurethane Load Wheel	X	
Cast Wheels		X

COMPANY INFORMATION



YALE PACIFIC

Suite 16.03, Level 16, Eclipse Tower, 60 Station Street, Parramatta NSW 2150, Australia

YALE ASIA

2 Venture Drive, #23-28 Vision Exchange, Singapore 608526

yale.com

SAFETY: Yale powered industrial trucks meet the design and construction requirements of local standards and regulations for the countries into which they are sold, including ANSI/ITSDF B56 (USA), Machinery Directive 2006/42/EC (EU), AS 2359 (Australia), and NR-11 (Brasil). Where permitted by local law, Yale products sold into countries outside of the EU or USA may be ordered in conformance with EU or USA requirements.

NOTICE: Care must be exercised when operating material handling equipment. Operators must be trained and must read, understand and follow the instructions contained in the operating manual. Products may be shown with optional equipment and/or features not available in all regions. Product performance may be affected by its condition, how it is equipped and the application. Specifications are subject to change without notice. Consult your Yale® Dealer if any of the information shown is critical to your application.

© 2026 Hyster-Yale Materials Handling, Inc., all rights reserved. YALE and YALE LOGO are trademarks of Hyster-Yale Materials Handling, Inc.